

## PREMIUM MULTI 5W40 SYNTHETIC MOTOR OIL

### DISCRIPTION

Premium Multi 5W40 Synthetic is a modern high performance synthetic based engine oil with special high-quality additives. Suitable for petrol, LPG and diesel engines with or without turbocharging in passenger cars and vans. As well as direct-injection diesel engines such as Common Rail, CDI and HDI.

A modern synthetic fuel-saving engine oil based on high quality synthetic base oils with a naturally high viscosity index and a balanced additive package to obtain the following properties:

### CHARACTERISTICS

- Lower fuel consumption.
- Very high thermal stability.
- Extended drain intervals.
- Stable viscosity at high temperatures.
- Excellent fluidity at low temperatures;
- Very high resistance to shearing.
- Very good detergent and dispersing properties.
- Smooth cold start.

### SPECIFICATIONS / INDUSTRIAL STANDARDS

ACEA A3/B4-04

API CF/SN

BMW Longlife 01

FIAT 9.55535-H2 / 9.55535-M2 / 9.55535-N2 / 9.55535-Z2

GM-LL A-025/B-025

MB 226.5/229.3

PORSCHE A 40

PSA B 71 2296

RN700/RN710

VW 502.00/505.00

### TECHNICAL SPECIFICATIONS

Viscosity class	-	SAE 5W40
Density 15° C	kg/m <sup>3</sup>	851
Kinematic viscosity, 40°C	mm <sup>2</sup> /s	89,9
Kinematic viscosity, 100°C	mm <sup>2</sup> /s	15,4
Viscosity index	-	182
Flash point, D92	°C	>213
Pour point	°C	-39
TBN mg	KOH/g	10
Sulphate ash	%mass	1,2

Contents: 60 litres / 200 litres



**RMC Lubricants B.V.** | Nikkelstraat 4, 6031 TR Nederweert, Nederland

T: +31 (0)495 54 42 16 | [info@rmclubricants.com](mailto:info@rmclubricants.com) | [www.rmclubricants.com](http://www.rmclubricants.com)

*No rights can be granted to this article and in addition, we are not liable for inaccuracies, which may unexpectedly be mentioned in this article.*