

PREMIUM 5W30 LONGLIFE III

MOTOR OIL

DISCRIPTION

Premium 5W30 LL III is a fully synthetic fuel-saving engine oil. Suitable for petrol, LPG and diesel engines, particularly Volkswagen, Audi, Skoda, Seat, BMW and Mercedes Benz with or without particulate filter.

A state-of-the-art, synthetic, fuel-saving motor oil for long drain intervals based on high performance synthetic base oils, to which advanced additives have been added to achieve the following properties:

CHARACTERISTICS

- Lower fuel consumption.
- Very good protection against foaming, corrosion and rust.
- Extended drain intervals.
- Stable viscosity at high temperatures.
- Very high resistance to shearing.
- Very good detergent and dispersing effect.
- Smooth cold start.

SPECIFICATIONS / INDUSTRIAL STANDARDS

ACEA A3/B3/B4/C2/C3

API CF/SM

BMW Longlife 04

FIAT 9.55535-S1 / 9.55535-S2

MB 229.51

PORSCHE

VW 504.00/507.00

TECHNICAL SPECIFICATIONS

Viscosity class	-	SAE 5W30
Density 15° C	kg/m ³	857
Kinematic viscosity, 40°C	mm ² /s	69
Kinematic viscosity, 100°C	mm ² /s	11,8
Viscosity index	-	168
Flash point, D92	°C	>200
Pour point	°C	-36

Contents: 60 litres / 200 litres

