

UNIVERSAL STOU 10W40

MOTOR OIL

DISCRIPTION

Universal STOU 10W40 is a multifunctional lubricant for engines and machines located in the public works and agriculture. It is an S.T.O.U. (Super Tractor Oil Universal) and is recommended to for the lubrication of engines, gearboxes, hydrostatic transmissions, hydraulic systems, wet brake systems and compressors.

The high-quality base oil and specific additives ensure good corrosion resistance, good anti-foaming properties and good shear resistance, ensuring optimal lubrication. All-round use where an S.T.O.U. 10W40 is required.

SPECIFICATIONS / INDUSTRIAL STANDARDS

ACEA E4-08/E7
API CI-4/GL4
ALLISON C4
Case New Holland CNH MAT 3525/3526
CAT TO2
JD J20C/J20D
MB 228.1
MF M1139/M1141/M1144/M1145
NH 410B
VICKERS M2950S
ZF-TE-ML 06B/06C/07B
ZF-TE ML 06A

TECHNICAL SPECIFICATIONS

Viscosity class	-	SAE 10W40
Density 15° C	kg/m ³	870
Kinematic viscosity, 40°C	mm ² /s	88
Kinematic viscosity, 100°C	mm ² /s	14
Viscosity index	-	165
Flash point, D92	°C	>215
Pour point	°C	-39
TBN mg	KOH/g	12,7
Sulphate ash	%mass	1,55

Contents: 60 litres / 200 litres

