

## SEAL CONDITIONER

### PROFESSIONAL OIL ANTI-LEAK ADDITIVE

#### DISCRIPTION

Eliminates oil leaks to the engine, hydraulic servo control and gearbox. Improves engine oil properties. Contains active synthetic components that regenerate the seals and make them smooth again. This additive does not affect the lubricating properties of the oil present in the engine.

#### CHARACTERISTICS

- Repairs and prevents oil leaks due to poor elasto-plastic seals.
- Reduces oil consumption.
- Reduces blue and smoky exhaust fumes.
- Harmless to the catalytic converter and particulate filter.
- Prevents damage of oil droplets from the engine or gearbox in the environment.

#### APPLICATION

Suitable for all petrol and diesel engines, manual transmission and hydraulic systems. For mineral, semi-synthetic and full synthetic oils (except brake oil).

#### INSTRUCTIONS FOR USE

Add Seal Conditioner to the engine oil when the engine is warm. Can be added to all mineral and synthetic oils. The product can be added to the existing engine oil at any time. The working effect of the seal will only work after a 600 - 800 km after the addition.

For power steering use ¼ dose (75 ml).

**The content (300 ml) is sufficient for 3 to 7 liters of oil.**

Contents: 12 x 300 ml/carton

