

AGRI UTTO 80W

TRANSMISSION OIL

DISCRIPTION

AGRI UTTO 80W is a universal tractor and transmission oil (UTTO) specially developed for lubricating hydraulic and transmission systems of the most common agricultural and road construction machines. Due to the special additive package, this oil can be used for a wide range of applications.

A high quality universal hydraulic and transmission oil based on pure refined base oils, to which specially selected additives have been added to provide the following to obtain properties:

CHARACTERISTICS

- Very low pour point
- Very good oxidation stability
- High and stable viscosity index
- Good EP and anti-wear properties
- Excellent anti-corrosion and anti-foam properties
- Favourable frictional properties, suitable for systems with wet brakes



SPECIFICATIONS / INDUSTRIAL STANDARDS

API GL4

AGCO POWERFLUID 821XL

ALLISON C4

Case New Holland CNH MAT 3505/3509/3525/3540

Case MS 1207/1210

CAT TO2

Ford ESN-M2C 86B/86C/134D

FNHA-2-C-200.00 / FNHA-2-C-201.00

John Deere J20B/J20C/J20D

Kubota UDT Fluid

Massey Ferguson CMS M 1135/1141/1143/1145

NH 410B

VCE WB 101

ZF-TE-ML 05F/03E/06K/17E/21F

TECHNICAL SPECIFICATIONS

Density 15° C	kg/m ³	887	
Kinematic viscosity, 40°C	mm ² /s	66,9	
Kinematic viscosity, 100°C	mm ² /s	10,7	
Viscosity index	-	148	
Flash point, D92	°C		>225
Pour point	°C	-35	
TBN mg	KOH/g	7,3	
Sulphate ash	%mass	1,19	

Contents: 60 litres / 200 litres