

PREMIUM GEAR 80W90 GL5

TRANSMISSION OIL

DISCRIPTION

PREMIUM GEAR 80W90 GL4 is a mineral transmission oil for manual transmissions and differentials. Provides excellent protection against metal to metal contact between gears, even under the toughest operating conditions and shock loads. Recommended for hypoid gears, hub gears, transmissions, PTOs and differentials, where an API GL-5 is required.

The specially selected additives have been added to obtain the following properties:

CHARACTERISTICS

- Very good oxidation stability.
- Excellent lubricating properties, even under the most extreme conditions.
- Very good anti-wear, anti-corrosion and anti-foaming properties.
- Low pour point.
- Very good "Extreme Pressure" properties.

SPECIFICATIONS / INDUSTRIAL STANDARDS

API GL-5
MAN 342 Typ M1
MB 235.0
Mil-L-2105D
ZF TE-ML 16B/17B/19B/21A

TECHNICAL SPECIFICATIONS

Density 15° C	kg/m ³	890
Kinematic viscosity, 40°C	mm ² /s	149
Kinematic viscosity, 100°C	mm ² /s	14,8
Viscosity index	-	98
Flash point, D92	°C	>232
Pour point	°C	-30

Contents: 60 litres / 200 litres

